

## RF Exposure Evaluation declaration

Product Name : Tablet: Wireless Tablet X860/X861;  
Dongle: Wireless Tablet Receiver X860/X861  
Model No. : Tablet: RCK-T07, RCK-T07S;  
Dongle: RCK-T07R, RCK-T07RS  
FCC ID. : Tablet: UBBRCKT07,  
Dongle: UBBRCKT07R

Applicant : WALTOP International Corp.

Address : 3F, No.6-8 Du-Sing RD., Hsin-Chu Science  
Park, Hsin-Chu City 30078, Taiwan, R.O.C.

Date of Receipt : 2010/12/30

Date of Declaration : 2011/02/09

Report No. : 111085R-RF Exposure

Report Version : V1.0

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

---

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product	Wireless Tablet
Test Mode	Mode 1: Transmit (Tablet)
Test Condition	RF Exposure Evaluation

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is  $-0.51\text{dBi}$  or 0.89 in linear scale.

#### Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm ( $\text{mW}/\text{cm}^2$ )
01	2402.00	0.8872	0.00016
39	2440.00	0.7516	0.00013
78	2479.00	0.6808	0.00012

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of  $1 \text{ mW}/\text{cm}^2$ .

Product	Wireless Dongle
Test Mode	Mode 2: Transmit (Dongle)
Test Condition	RF Exposure Evaluation

### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is  $-3.67\text{dBi}$  or 0.43 in linear scale.

### Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm ( $\text{mW}/\text{cm}^2$ )
01	2402.00	0.1122	0.00001
39	2440.00	0.1202	0.00001
78	2479.00	0.1000	0.00001

The power density  $P_d$  (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of  $1 \text{ mW}/\text{cm}^2$ .